



AM-BOSS
ACCESS LADDERS



OPERATING & MAINTANANCE PROCEDURE

AM-BOSS POPI (Pull-Out / Push-In) ACCESS LADDER

OPENING

Face ladder and hold ladder firmly with both hands. Commence walking backwards, pulling access ladder towards you until ladder comes to a stop. Lock ladder into position using brake located on each wheel.

In compliance with your local OH&S requirements, all ladders of any kind must be climbed up or down facing the ladder.

CLOSING

Face ladder and with both hands firmly holding the ladder, unlock the ladder by releasing the brake on each wheel. Walking forward, pushing ladder back and into vertical position. Lock wheels in place using the brakes on each wheel.

NEVER PULL-OUT OR PUSH-IN LADDER WITH SOME-ONE ON THE LADDER.

MAINTENANCE

ALL MOVING PARTS ARE FACTORY PRE-LUBRICATED. ENSURE TRACKING SYSTEM IS GREASED / LUBRICATED ANNUALLY. SHOULD OPERATION OF THE UNIT BE IN EXCESS OF 3 TO 5 TIMES A DAY, ALL MOVING PARTS MUST BE LUBRICATED ONCE EVERY TWO MONTHS.

Inspection of the whole system MUST BE carried out minimum once a year and action taken as required